


JLS8420	24	40	AA	BB	CC	DD
Model	Voltage	Width	CCT	IP	CRI	Length
	24: 24V	40: 40mm	27: 2700K 30: 3000K 40: 4000K	33: IP33 (Dry)	80: 80+	




CCT	Power	Brightness	Luminous Efficacy
2700K	9.1 W/ft	1081 lm/ft	119 lm/W
3000K	9.1 W/ft	1185 lm/ft	130 lm/W
4000K	9.1 W/ft	1239 lm/ft	136 lm/W

Project	
Qty	
Date	
Client	

Standard CCT



Waterproof Solution



IP33

No waterproof

Dry location

LED Type	SMD2835 white
Input Voltage	24VDC
Beam Angle	120°
CRI	80+
Power	30W/m (9.1W/ft.)
Current	1.25A/m (0.38A/ft)
Brightness	1081lm/ft (2700K); 1185lm/ft (3000K); 1239lm/ft (4000K)
Length/ Reel	2.5m(8.2ft)
Cut Length	50mm/unit (1.97in/unit)
Max. Length (No Voltage drop)	10 ft
IP Grade	IP33
Operating Temperature	-20°C~45°C
Environment Humidity	40-70% RH
LED CCT	2700K/ 3000K/ 4000K
Dimming Method	0-10V, RX, PWM, Triac, RF, Bluetooth, WIFI etc.
Certification	UL, CE, RoHS

DIMENSION

